

ARMY RESEARCH LABORATORY



## Energy Cost of Walking in Four Types of Snowshoes

Joseph J. Knapik  
Charles A. Hickey, Jr.  
Samson V. Ortega, Jr.  
James R. Nagel  
Rene de Pontbriand

ARL-TR-1175

OCTOBER 1996

DTIC QUALITY INSURED

19961206 194

Oxylog2® is a registered trademark of P.K. Morgan Limited.

Polar Vantage XL® is a registered trademark of Polar Electro Oy.

The findings in this report are not to be construed as an official Department of the Army position  
unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of  
the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

# **Army Research Laboratory**

Aberdeen Proving Ground, MD 21005-5425

---

ARL-TR-1175

October 1996

---

## **Energy Cost of Walking in Four Types of Snowshoes**

Joseph J. Knapik  
Charles A. Hickey, Jr.  
Samson V. Ortega, Jr.  
James R. Nagel  
Rene de Pontbriand  
Human Research & Engineering Directorate

---

Approved for public release; distribution is unlimited.

---

---

## Abstract

---

Energy cost was examined while four Marines walked at 4 km/hr on an open field with each of four snowshoes. Snowshoes were the Pride Assault, Montana, British Assault, and the U.S. Army Standard. The grade of the field was about 2.4% and the Marine walked once downhill and once uphill with each snowshoe. Expired respiratory gases were collected continuously during each walk. On the downhill portion of the course, average  $\pm$  standard deviation (SD)  $\text{VO}_2$  values were  $1.25 \pm 0.13$ ,  $1.46 \pm 0.11$ ,  $1.31 \pm 0.13$ , and  $1.22 \pm 0.20$  l/min for the Pride, Montana, British, and Standard snowshoes, respectively ( $p=0.01$ ); the Pride and Standard snowshoes had significantly lower energy cost than the Montana ( $p=0.05$ ). On the uphill portion of the course, average  $\pm$  SD  $\text{VO}_2$  values were  $1.58 \pm 0.12$ ,  $1.7 \pm 0.14$ ,  $1.62 \pm 0.21$ , and  $1.5 \pm 0.06$  l/min for Pride, Montana, British, and Standard snowshoes, respectively ( $p=0.06$ ). Data suggested that several characteristics may be favorable from an energy cost perspective: 1) a foot hinge and binding system that allows the snowshoe to be dragged across the snow, 2) an upturned front that pushes snow away and allows a more horizontal displacement of the snowshoe during locomotion, and 3) a lower mass-to-surface-area ratio. Further research will be necessary to determine the relative importance of these design characteristics, given the small number of subjects.



## ACKNOWLEDGMENTS

We thank the Marines who enthusiastically volunteered for this study. The cooperation and assistance of Gunnery Sergeant Hopkins of the 2/7 Marines was invaluable. Thanks also to CPT Lewis Vogler, Jr., from the USMC Mountain Warfare Training Center for handling the logistics and the organization of the study and to Mike Kosinski and Mark Ditmore who developed the manual planimetry techniques to obtain the snowshoe surface area measurements.

## CONTENTS

EXECUTIVE SUMMARY .....	3
INTRODUCTION .....	5
BACKGROUND .....	6
OBJECTIVE .....	8
METHODS .....	8
Subjects .....	8
Anthropometry .....	9
Apparatus .....	9
Procedures .....	19
Data Analysis .....	21
RESULTS .....	21
DISCUSSION .....	26
Comparisons Among Snowshoes .....	26
Comparisons Among Studies .....	29
Snow Conditions .....	30
REFERENCES .....	33
DISTRIBUTION LIST .....	37
REPORT DOCUMENTATION PAGE .....	45
FIGURES	
1. Top View of Pride Assault Snowshoe .....	10
2. Bottom View of Pride Assault Snowshoe .....	11
3. Top View of Montana Snowshoe .....	12
4. Bottom View of Montana Snowshoe .....	13
5. Top View of British Assault Snowshoe .....	15
6. Bottom View of British Assault Snowshoe .....	16
7. Top View of U.S. Army Standard Snowshoe .....	17
8. Bottom View of U.S. Army Standard Snowshoe .....	18
9. Relationship of Oxygen Uptake and Snowshoe Mass-to-Surface-Area Ratio ..	27

## TABLES

1. Order of Snowshoe Presentation . . . . .	21
2. Body Composition and Anthropometric Characteristics of the Marines . . . . .	22
3. Physical Characteristics of the Four Snowshoes . . . . .	22
4. Stride Length and Flotation Measures . . . . .	23
5. Actual Speed of Walking During Snowshoe Testing . . . . .	23
6. Cardiorespiratory Values for the Four Snowshoe Models on the Downhill Portion of the Course . . . . .	24
7. Cardiorespiratory Values for the Four Snowshoes on the Uphill Portion of the Course . . . . .	25
8. Correlation Coefficients Between Measures of Snowshoe Depression and Oxygen Consumption . . . . .	25
9. Correlations Between Snowshoe Characteristics and Average Oxygen Consumption . . . . .	26
10. Statistical Power Analysis of Snowshoe Types Based on Data from This Study . . . . .	28
11. The Energy Cost of Walking in Snowshoes in Various Studies . . . . .	30
12. Estimates of Metabolic Rates, Energy Expenditure Rates, and $\text{VO}_2$ (from Pandolf equation) Compared to Actual $\text{VO}_2$ During Uphill Walking at 2.4% Grade . . . . .	31

## EXECUTIVE SUMMARY

Energy cost was examined while Marines walked in each of four snowshoes: the Pride Assault, Montana, British Assault, and the U.S. Army Standard. Four male Marine volunteers wearing only battle dress uniforms (BDU) and Gortex parkas walked with each snowshoe at 4 km/hr on an open field. Walking velocity was established by a pace setter who called the speed every 30 m; the Marine adjusted his pace based on this feedback. Grade of the field was about 2.4% and the Marine walked once downhill and once uphill with each snowshoe. Each walking segment was 336 meters long and took about 5 minutes to complete. While the Marines walked, heart rates and expired respiratory gases were collected continuously. Heart rate was measured with a Polar Vantage XL® heart rate device, and expired gases analyzed for oxygen content ( $\text{VO}_2$ ) using an Oxylog2®. Overall snowshoe flotation was measured from snowshoe prints by averaging the depth of depression on the medial, lateral, and posterior sides. Snow conditions were 8 cm of new powder on a 60-cm base. On the downhill portion of the course average  $\pm$  standard deviation (SD)  $\text{VO}_2$  values were  $1.25 \pm 0.13$ ,  $1.46 \pm 0.11$ ,  $1.31 \pm 0.13$ , and  $1.22 \pm 0.20$  l/min for the Pride, Montana, British, and Standard snowshoes, respectively ( $p=0.01$ ). Post hoc analysis indicated that the Pride and Standard snowshoes had significantly lower energy cost than the Montana ( $p=0.05$ ). On the uphill portion of the course average  $\pm$  SD  $\text{VO}_2$  values were  $1.58 \pm 0.12$ ,  $1.78 \pm 0.14$ ,  $1.62 \pm 0.21$  and  $1.51 \pm 0.06$  l/min for Pride, Montana, British, and Standard snowshoes, respectively ( $p=0.06$ ). There were no significant differences among the snowshoes on overall flotation; average depth of depression was about 5 cm. The Pride and Standard snowshoes differed from the Montana in several characteristics, suggesting that these characteristics may be favorable from an energy cost perspective. These characteristics were 1) a foot hinge and binding system that allows the snowshoe to be dragged across the snow, 2) an upturned front that pushes snow away and allows a more horizontal displacement of the snowshoe during locomotion, and 3) a lower mass-to-surface-area ratio (lighter snowshoe combined with a greater area on the snow). Further research will be necessary to determine the relative importance of these design characteristics, given the small number of subjects in this investigation.

## THE ENERGY COST OF WALKING IN FOUR TYPES OF SNOWSHOES

*Weather is not only to a great extent the controller of the conditions of ground but also of movement.*

-- Major General J.F.C. Fuller, *The Foundations of the Science of War*, 1926

*...the Russian land which he dreams of enslaving will be strewn with his bones. We will pursue tirelessly. Let winter, blizzards, and the cold come. We know them.*

-- Field Marshall Prince Mikhail Kutuzov, 1812, speaking with his troops during Napoleon's invasion of Russia (Sbornik dokumentov, 1955).

### INTRODUCTION

Cold climates with large amounts of ground snow cover pose significant challenges for military operations. One of these challenges is the ability of foot soldiers to traverse over the snow. A dramatic example of how military success was influenced by effective mobility across snow occurred in the winter of 1939-1940 when the Soviet Army invaded Finland. At the Battle of Suomussalmi, the Finnish Ninth Infantry Division defeated the combined strength of the Soviet 163th Infantry Division and 44th Motorized Rifle Division despite the Soviet's two- or three-to-one numerical advantage. The Finnish Army had trained in the snow and knew how to quickly and efficiently move across it (Thompson, 1995).

Two major methods of movement in deep snow are skis and snowshoes. Snowshoes are by far the easier method for American soldiers to learn; it has been estimated that skillful movement over open terrain can be acquired in about 1 hour of training (Thompson, 1995). Despite the perceived usefulness of snowshoes for mobility over snow, there are few investigations examining the effectiveness of this mode of transportation for military operations (Hickey, Knapik, Ortega, & Nagel, 1996; Hickey, Hanlon, & Oblak, 1994).

One characteristic of the snowshoe that can become very important in a military environment is the energy cost. Compared to temperate environments, cold climates require soldiers to carry a greater quantity of clothing and equipment in order to combat weather-related problems. This additional load taxes the soldier's energy reserves. A snowshoe that has a low energy cost would be favored over one with a higher energy cost. The lower energy cost item would help the soldier conserve strength for other tasks.

The major purpose of this investigation was to determine the energy cost of four snowshoes. A secondary purpose was to determine some of the factors that may account for the differences in energy cost among the snowshoes.

## BACKGROUND

It is often assumed that human energy cost is increased in cold weather. Cold exposure can increase energy cost if the individual is inadequately clothed and shivering occurs. Shivering is the forcible contraction of one muscle group against its antagonist and can increase resting energy expenditure as much as 5 times (Adolph & Molnar, 1946). On the other hand, there is probably little or no measurable increase in energy expenditure in an adequately clothed individual because a microclimate is created around the body through the trapping of warm air in clothing which maintains body temperature. Some increases in energy expenditure might be expected to be attributable to a) warming and humidifying cold air breathed into the body, b) warming of cold air brought into the clothing, and c) the additional weight of equipment and clothing that must be carried in field environments (Askew, 1989; Buskirk & Mendez, 1967). However, during controlled laboratory conditions, energy cost is the same in a temperate (26° C to 20° C) and a cold (5° C to -20° C) environment, provided the exercise intensity is sufficient to cause heat transfer from the body to the environment (Patton & Vogel, 1984; Stromme, Andersen, & Elsner, 1963). Further, with physical activity of sufficient intensity, core and extremity temperature can be easily maintained (Virokannas, 1996). Patton and Vogel (1984) had subjects perform cycle ergometer exercise at 17±5 watts (approximately 75% VO<sub>2</sub> max) to exhaustion and found no difference in energy cost whether subjects exercised at -20° C or +20° C.

Much work has been done on the energy cost of human locomotion. Energy cost increases in a systematic manner with increases in body mass, load mass, velocity, and/or grade (Bobbert, 1960; Borghols, 1978; Goldman & Iampietro, 1962; Soule, Pandolf, & Goldman, 1978). Type of terrain also influences energy cost (Haisman & Goldman, 1974; Pandolf, Haisman, & Goldman, 1976; Soule & Goldman, 1972). Pandolf, Givoni, and Goldman (1977) used these relationships to develop an equation for predicting energy cost of locomotion with loads:

$$M_w = 1.5 \cdot W + 2.0 \cdot (W+L) \cdot (L/W)^2 + T \cdot (W+L) \cdot (1.5 \cdot V^2 + 0.35 \cdot V \cdot G)$$

in which  $M_w$  = Metabolic cost of walking (watts)  
 $W$  = Body mass (kg)  
 $L$  = Load mass (kg)

T = Terrain factor (coefficients shown below)

1.0 = Black top road

1.1 = Dirt road

1.2 = Light brush

1.5 = Heavy brush

1.8 = Swampy bog

2.1 = Loose sand

V = Velocity or walk rate (m/sec)

G = Slope or grade (percent)

Critical to this equation is the terrain factor. The terrain factor is an empirically derived number based on studies examining energy cost in various terrains. Energy expenditure during walking in the snow appears to be largely dependent on the depth to which the individual sinks into the snow (Heinonen, Karvonen, & Ruosteenoja, 1959; Pandolf et al., 1976; Ramaswamy, Dua, Viswanathan, Madhavia, & Srivastava, 1966). Pandolf et al. (1976) demonstrated a rise in energy cost as the depth of depression increased. The terrain factor for walking in snow could be estimated from the equation:

$$T = 1.30 + 0.082D$$

in which T = Terrain Factor and D = depth of the depression (in cm).

The Pandolf equation was developed for predicting the energy cost of locomotion with boots. Placing snowshoes on the boot complicates the metabolic picture. In addition to the factors mentioned (body mass, load mass, velocity, and grade), certain characteristics of the snowshoe might be expected to influence energy cost. A snowshoe with a larger surface area may result in greater flotation (i.e., how well the snowshoe keeps a person from sinking into the snow), thus reducing the depth of depression, and consequently reducing energy cost (Pandolf et al., 1976; Ramaswamy et al., 1966). The total mass of the snowshoe may also be important. Any increase in load mass will increase energy cost, but loads carried on the feet are especially expensive since they result in an energy cost five to seven times higher than an equivalent load carried on the upper body (Legg & Mahanty, 1986; Soule & Goldman, 1969). For each 1 kg added to the foot, the increase in energy expenditure is 7% to 10% (Catlin & Dressendorfer, 1979; Jones, Toner, Daniels, & Knapik, 1984; Legg & Mahanty, 1986; Soule & Goldman, 1969). Thus, factors relating to flotation, surface area, and snowshoe mass must be considered in the energy cost of walking in snowshoes.

Few studies have examined energy cost during locomotion in snowshoes and all these studies have neglected critical variables. Buskirk et al. (1956) made nine determinations on eight men walking at 3.7 km/hr. They found an average energy cost of 6.21.1 kcal/min or an oxygen uptake of 1.28 l/min (17.5 ml/kg\*min). Neither the snowshoe characteristics nor depth of snow is reported. Rodgers, Buck, and Klopping (1965) report individuals walking at 3.7 km/hr with snowshoe prints about 9 cm deep. They estimated that oxygen uptake was 2.45 l/min (35ml/kg\*min) for one man. They do not provide the type of snowshoe used or its characteristics. Allen and O'Hara (1973) studied nine infantrymen carrying equipment estimated at 23 to 27 kg, traveling at 2 to 3.6 km/hr. They found an average energy expenditure of  $4.83 \pm 1.51$  kcal/min or  $0.98 \pm 0.30$  l/min. Walking pace was highly variable and the depth of depression and snowshoe type were not reported. Worsley (1974) reported a number of soldiers walking in snowshoes with packs at various speeds where the depth of depression did not exceed 5 cm. During the conditions of their study, oxygen uptake (ml/kg\*min) could be predicted from the equation  $-1.3 + 0.33 * \text{speed (m/min)}$  over a range of speeds from about 40 to 100 m/min (2.4 to 6 km/hr). However, pack mass was not provided, nor was the grade of the terrain the soldiers traversed.

## OBJECTIVE

The major objective of this investigation was to measure the energy cost of locomotion in four types of snowshoes. The secondary objective was to examine some factors that may influence energy cost of snowshoeing.

## METHODS

### Subjects

Subjects were four Marines who volunteered for this investigation after a full briefing about the purposes and risks. They signed an informed consent statement in compliance with Army Regulation 70-25. The study was approved by the institutional Human Use Review Committee.

Marines had previously trained one day with each snowshoe before the energy cost studies as part of another investigation (Hickey et al., 1996). Training consisted of identical morning and afternoon sessions. These involved a 30- to 45-minute walk in the snowshoe, a run up and down a steep hill and a sprint on a 75-m assault course. On the walk, a variety of terrain was encountered, including level areas, rolling hills, and steep slopes (uphill and downhill). The



75-m sprint involved completing the distance as fast as possible while assuming a prone rifle-firing position twice at specific intervals on the course. Marines wore the snowshoes around the camp during the time they were not being tested.

## Anthropometry

Marines' total body mass was obtained from a digital scale (Seca) and stature from an anthropometer (GPM). Age was determined from the date of their last birthday. Circumferences were obtained from the neck and abdomen using a fiberglass tape measure (Gulick). Body fat was estimated from anthropometric measurements (Vogel, Kirkpatrick, Fitzgerald, Hodgdon, & Harman, 1984) and fat-free mass by subtracting body fat mass from total body mass.

Trochanterion height (total leg length) was measured with an anthropometer from the floor to the femoral trochanter with the subject in the standing position, heels together, and weight evenly distributed on each foot (Gordon et al., 1989). Calf length was measured with an anthropometer between the knee joint line and tip of the medial malleolus (tibia distance) with the subject in a seated position and knees crossed (Lohman, Roche, & Martorell, 1988). Thigh length was measured with a fiberglass tape from the midpoint of the inguinal ligament to the proximal edge of the patella with the subject standing and the measured leg on a chair such that the knee was at a 90° angle (Lohman et al., 1988). All these measurements were made on the right leg.

## Apparatus

### Snowshoes

Four snowshoes (the Pride Assault, the Montana, the British Assault and the U.S. Army Standard snowshoe [trail magnesium]) were tested. The Pride Assault snowshoe (see Figures 1 and 2) consisted of an aluminum frame to which a solid plastic membrane was attached with 20 plastic loops. The front of the frame was turned upward. The boot binding system (see Figure 1) was attached to the aluminum frame by a plastic-covered piece of steel that allowed the binding to pivot as the subject walked. The binding consisted of single piece of aluminum with upturned sides to prevent lateral and medial boot slippage. When the boot entered the binding, a clip at the rear forced the boot against a front cable and firmly locked it into the binding. A single adjustable strap on the rear clip was secured around the ankle to minimize the possibility of the clip coming off. On the underside of the Pride were two crampons (see

Figure 2), one of which pivoted with the binding as the subject walked. The other crampon was fixed under the snowshoe at about the level of the heel.




Figure 1. Top view of pride assault snowshoe.




Figure 2. Bottom view of pride assault snowshoe.




Figure 3. Top view of Montana snowshoe.






Figure 4. Bottom view of Montana snowshoe.

The Montana snowshoe (see Figures 3 and 4) was a rubber tire into which holes had been drilled. Fabric webbing was looped through some of these holes and the webbing formed a crisscrossed network inside the tire. The nine pieces of webbing were riveted at crossing points. The boot binding system consisted of three straps riveted to the webbing; all three straps were adjustable using buckles. Two straps ran over the tops of the boot and one across the heel.

The British Assault snowshoe (see Figures 5 and 6) consisted of a plastic (polyvinyl chloride [PVC]) frame with nine crisscrossed straps riveted at crossing points. The boot binding system consisted of 1) a plastic strap that ran over the top of the boot, 2) a fabric strap for the front of the ankle, and 3) a fabric strap that ran from the front of the boot to around back of the heel. All three straps were adjustable with buckles. On the underside of the snowshoe (see Figure 6) were two crampons arranged at about a 45° angle to the long axis of the snowshoe. The crampons were attached to the aluminum frame and to a single thin strip of metal near the front of the snowshoe.

The U.S. Army Standard snowshoe (see Figures 7 and 8) had a metal frame with two metal supports approximately perpendicular to the frame. The metal frame tapered to a long tail in the rear of the snowshoe and the front of the snowshoe was turned upward. Plastic-covered wires crisscrossed the frame. The boot binding system consisted of three fabric straps that went around the top of boot, heel, and ankle. The straps were adjustable with buckles.

#### Measurement of Snowshoe Characteristics

The mass of each snowshoe was measured using a digital scale. Length and width were measured with a ruler at the longest portions of each snowshoe.

Surface areas were determined by manual planimetry. Two outlines of each snowshoe were traced on a large sheet of paper. Tracings were performed on the flat and anterior curved portions of the snowshoe. The flat portion was that part of the snowshoe which was in contact with the surface when the snowshoe sat on a level platform. The curved portion was the front upturned part of the snowshoe (only present on the Pride and Standard models). Curvature outlines were obtained by rolling the snowshoe forward on the paper and then tracing this portion. To determine the limit of the curvature, 1) the snowshoe was placed back down on the tracing a second time, 2) a thin ruler was slipped under the front part of the shoe until the snowshoe stopped the ruler, 3) the snowshoe was removed, and 4) a straight line was drawn

across the tracing where the ruler rested. The curved area was the area encompassed by the line and front part of the shoe.




Figure 5. Top view of British assault snowshoe.




Figure 6. Bottom view of British assault snowshoe.






Figure 7. Top view of U.S. Army standard snowshoe.



Figure 8. Bottom view of U.S. Army standard snowshoe.

To gauge flotation, the depth of depression was measured. Flotation is the inverse of depression, that is, the greater the depression, the less the flotation. Depression was measured with a ruler after Marines began walking in the snow. A straight edge was placed horizontally across the snowshoe print. A ruler was used to make four vertical measurements on the lateral, medial, and posterior portions of the snowshoe imprint. The deepest impression was also measured. To obtain a measure of overall depression, the lateral, medial, and posterior values were summed and averaged. The deepest depression was not included in the measure of overall depression because the characteristics of some snowshoes would have an unduly large influence on this measure (i.e., the crampon on the Pride or the toe pivot on the Standard).

### Heart Rate

Heart rate was determined using a Polar Vantage XL<sup>®</sup> heart rate watch (Polar USA, Stamford, Connecticut). The device consisted of a sensor strap and watch. The subject wore the sensor strap around his chest. The watch was placed on the Oxylog2<sup>®</sup> device to allow technicians to read it easily. The strap contained electrodes that detected electrical signals from the heart and transmitted them to the watch.

### Oxylog2<sup>®</sup> Device

The Oxylog2<sup>®</sup> device (PK Morgan, Chatham, United Kingdom) was designed to measure oxygen consumption ( $\text{VO}_2$ ) and ventilation ( $\text{V}_E$ ) in ambulatory subjects. The subjects' expired air was passed to the central Oxylog2<sup>®</sup> unit which contained a FIGARO KE-25 oxygen fuel type cell. The  $\text{PO}_2$  difference between the inspired and expired air was measured in the instrument, and the volume of oxygen extracted was calculated. A turbine flow meter attached to the air intake side calculated the volume of the subjects' inspired air. A display on the device provided the  $\text{VO}_2$  and  $\text{V}_E$ , which were averaged as minute values.

Marines wore a large pediatric mouth breathing face mask (Hans Rudolph Inc., Kansas City, Missouri, Series 7970) connected to the central Oxylog2<sup>®</sup> unit with Warren Collins (Braintree, Massachusetts) plastic spiral tubing. The Oxylog2<sup>®</sup> turbine flow meter was connected to the inlet valve of the face mask with Warren Collins molded couplers. The entire device weighed 2.3 kg.

### Procedures

The snowshoe course was situated on a meadow in the Sierra Mountains of California

near the Marine Corps Mountain Warfare Training Center, Bridgeport, California (Sonora Pass Area). A 336-meter course was delineated on a helicopter landing zone. The course was not flat. An estimate of the slope obtained using survey techniques found the grade to be 2.4%.

All measurements were made on a single day and it had snowed the night before. Conditions were about 8 cm of powder snow on a base of about 60 cm of crust. In the days before the snowfall, temperatures had routinely achieved 10° C during the day, dropping below 0° C at night. Thus, the base snow had repeatedly frozen and thawed. Temperatures during the energy cost testing ranged from -3° C to 2° C.

Procedures during the testing were as follow. The Marines' mass in BDUs was obtained from a digital scale. They then donned the Oxylog2® device and the mask was fitted. The central Oxylog2® unit was contained in an insulated carrying case that was suspended from the subject's hips. The case was stabilized with straps across the Marine's shoulders and waist. While the Marine was changing snowshoes, he removed the mask by pulling it down to his neck. Just before walking, he put the mask back on and waited 1 minute before beginning to walk.

One of the investigators walked with each Marine and provided pacing information. The Marine was told that the goal was to achieve a pace of 4 km/hr (1.12 m/sec, 2.5 mi/hr). Poles were placed in the snow along the course, alternating every 20 m and 10 m. Between the 20-m markers, the investigator obtained the time to cover the distance. During the 10-m distance, the investigator consulted a chart relating time to distance and the Marine was provided his current speed. Information given the Marine was in the form of the speed for the previous 20-m segment (e.g., "4.2, that is a little fast; slow it down just a bit"). This process was repeated every 30 m. Marines were easily able to adjust their pace within 1 to 2 minutes of walking. Time to complete the entire 336-m distance was recorded at the end of the walk and converted to average speed for the distance.

Marines completed two walks with each of the four snowshoe models. Marines walked for about 5 minutes on the downhill leg of the course, then reversed direction and walked for about 5 minutes on the uphill leg. They then changed snowshoes and repeated the process. The order of presentation of the snowshoes is shown in Table 1. Marines always walked on fresh snow by progressively moving to the eastern side of their previous tracks. Measurements were obtained from the digital displays on the Oxylog2® and heart rate monitors at 3.5 minutes and at 5 minutes of the walk. Ventilation (l/min), oxygen uptake (l/min), and heart rate (beats/min) were recorded on paper.

Table 1

## Order of Snowshoe Presentation

Marine identification number	Presentation order			
	1	2	3	4
1	Pride	Montana	British	Standard
2	Montana	Standard	Pride	British
3	British	Pride	Standard	Montana
4	Standard	British	Montana	Pride

## Data Analysis

Data were analyzed using a one-way repeated measures analysis of variance (ANOVA), testing the hypothesis of no difference among snowshoes. When significant differences were found, differences between snowshoes were determined with the Tukey Honestly Significant Difference (HSD) Test. Pearson product moment correlations were used to examine the relationship between oxygen consumption and flotation measures. In order to examine the relationship between snowshoe characteristics and oxygen consumption, Pearson product moment correlations were performed between the average oxygen consumption for each snowshoe (uphill and downhill legs separately) and the snowshoe characteristics.

## RESULTS

The physical characteristics of the four Marines are shown in Table 2.

The physical characteristics of the snowshoes are presented in Table 3. The two surface area measurements did not differ by more than 0.6%, so the values were averaged. The correlation between snowshoe mass and surface area was 0.67 ( $p=0.33$ ).

Table 2

## Body Composition and Anthropometric Characteristics of the Marines

	Stature (cm)	Body mass (kg)	Body fat (percent)	Fat mass (kg)	Fat-free mass (kg)
Mean	174.2	73.2	16.5	12.5	60.7
SD	4.9	4.5	8.2	7.8	4.1

---

	Neck circumference (cm)	Abdominal circumference (cm)	Trochanterion height (cm)	Thigh length (cm)	Calf length (cm)	Body mass with uniform (kg)
Mean	36.7	83.4	91.6	39.5	37.2	77.6
SD	1.8	9.4	5.5	3.2	2.7	9.6

Table 3

## Physical Characteristics of the Four Snowshoes

Manufacturer	Model	Size (cm)		Mass (kg)	Surface area (cm <sup>2</sup> )		Mass to surface area ratio (gm/cm <sup>2</sup> )
		length	width		entire shoe	curve	
Pride	Assault	74	22	2.4	1393	230	1.72
Montana	RWT	52	34	3.0	1649		1.82
British	Assault	46	30	2.0	1302		1.54
Standard	Trial	120	28	2.6	1892	335	1.37
	magnesium						

Table 4 shows the measurements made on stride length and depression depth for each of the four snowshoes. A lower number for depression would indicate better flotation (less depression into the snow). There were no significant differences among the snowshoes on any measure.



Table 4

## Stride Length and Flotation Measures

	Stride length (cm)	Flotation measures				
		Medial depression (cm)	Lateral depression (cm)	Rear depression (cm)	Deepest depression (cm)	Overall depression (cm)
Pride	73.5 $\pm$ 2.3	5.4 $\pm$ 0.7	5.0 $\pm$ 0.8	5.5 $\pm$ 0.5	6.9 $\pm$ 0.5	5.3 $\pm$ 0.9
Montana	74.4 $\pm$ 3.1	5.3 $\pm$ 0.2	5.5 $\pm$ 0.3	6.0 $\pm$ 0.9	6.0 $\pm$ 0.4	5.6 $\pm$ 0.7
British	73.2 $\pm$ 1.7	4.9 $\pm$ 0.8	5.3 $\pm$ 0.7	5.7 $\pm$ 0.7	5.7 $\pm$ 0.5	5.3 $\pm$ 1.3
Standard	70.7 $\pm$ 3.1	5.5 $\pm$ 0.3	4.3 $\pm$ 0.5	5.0 $\pm$ 0.5	5.8 $\pm$ 0.3	4.9 $\pm$ 0.8
F-value	0.38	0.18	0.70	0.65	2.13	0.38
p-value	0.77	0.91	0.57	0.60	0.17	0.77

Table 5 shows the speed at which Marines completed the 5-minute walks on both the uphill and downhill legs of the course. There were no significant differences among the snowshoes.

Table 5

## Actual Speed of Walking During Snowshoe Testing

	Speed on uphill (km/hr)	Speed on downhill (km/hr)
Pride	4.1 $\pm$ 0.0	4.1 $\pm$ 0.1
Montana	4.1 $\pm$ 0.1	3.9 $\pm$ 0.2
British	4.1 $\pm$ 0.1	4.2 $\pm$ 0.4
Standard	4.0 $\pm$ 0.2	4.0 $\pm$ 0.1
F-value	1.88	1.19
p-value	0.20	0.37

Table 6 shows the cardiorespiratory values for the four models of snowshoes when Marines were on the downhill leg of the course. These are the average of the values taken at 3.5 minutes and 5 minutes since a paired t-test showed no difference between the two periods for any measure. The Tukey test on the  $\text{VO}_2$  values revealed that the Pride and the Standard snowshoes had a significantly lower energy cost than the Montana ( $p < 0.05$ ) but the British did not differ from any other snowshoe (critical difference = 0.17 for absolute  $\text{VO}_2$  (l/min) and 2.36 for relative  $\text{VO}_2$  (ml/kg\*min). For  $\text{V}_E$ , the Tukey test indicated that the Montana produced significantly higher values than any of the other three snowshoes but there were no significant differences among the Pride, British, or Standard shoes (critical difference = 5.4).

Table 6  
Cardiorespiratory Values for the Four Snowshoe Models on the  
Downhill Portion of the Course

	Heart rate (beats/min)	$\text{VO}_2$ (l/min)	$\text{VO}_2$ (ml/kg*min)	$\text{V}_E$ (l/min)
Pride	122.9±14.2	1.25±0.13	17.4±3.2	24.5±6.1
Montana	136.0±11.1	1.46±0.11	20.2±2.7	30.0±6.2
British	130.4±14.4	1.31±0.13	18.2±3.7	24.4±4.3
Standard	123.3±7.3	1.22±0.20	16.8±2.3	20.6±2.6
F-value	2.09	7.79	7.36	8.69
p-value	0.17	0.01	0.01	0.01

Table 7 shows the cardiorespiratory values for the four snowshoes when Marines were on the uphill portion of the course. The rank of snowshoes with regard to energy cost and heart rate was similar to the downhill portion (see Table 6).

Table 8 shows the Pearson product moment correlation coefficients between the flotation measures and oxygen uptake for each snowshoe. The pattern of correlations suggests that lower energy cost is associated with less depression for the Pride and Montana, but this pattern is not seen with the British or Standard snowshoes.



Table 7  
Cardiorespiratory Values for the Four Snowshoes on the  
Uphill Portion of the Course

	Heart rate (beats/min)	VO <sub>2</sub> (l/min)	VO <sub>2</sub> (ml/kg*min)	V <sub>E</sub> (l/min)
Pride	143.4±14.6	1.58±0.12	22.0±4.0	32.6±9.7
Montana	154.6±7.3	1.78±0.14	24.5±2.8	36.7±10.8
British	151.4±11.1	1.62±0.21	22.6±4.9	32.2±9.0
Standard	143.6±8.4	1.51±0.06	21.0±3.3	30.1±5.1
F-value	3.35	3.69	3.47	1.96
p-value	0.07	0.06	0.06	0.19

Table 8  
Correlation Coefficients Between Measures of Snowshoe  
Depression and Oxygen Consumption

		Deepest depression	Overall depression
VO <sub>2</sub> (l/min)	Pride (downhill)	0.96	0.65
	Pride (uphill)	0.51	0.31
	Montana (downhill)	0.69	0.24
	Montana (uphill)	0.48	0.89
	British (downhill)	-0.66	-0.20
	British (uphill)	0.06	0.56
	Standard (downhill)	0.11	-0.26
	Standard (uphill)	0.16	-0.17
VO <sub>2</sub> (ml/kg*min)	Pride (downhill)	0.81	0.71
	Pride (uphill)	0.50	0.50
	Montana (downhill)	0.83	0.26
	Montana (uphill)	0.82	0.72
	British (downhill)	-0.53	-0.09
	British (uphill)	-0.15	0.36
	Standard (downhill)	0.01	-0.33
	Standard (uphill)	0.04	-0.29

Table 9 displays correlations between various snowshoe characteristics and average oxygen uptake. The mass-to-surface-area ratio demonstrated the highest relationships and Figure 9 displays this. Examination of Figure 9 suggests that the Montana, British, and Standard snowshoes demonstrate proportional increases in oxygen consumption with increasing mass-surface area. The Pride, however, departs from this trend showing less of an increase for its surface area.

Table 9  
Correlations Between Snowshoe Characteristics and  
Average Oxygen Consumption

Snowshoe characteristic	Oxygen consumption	
	downhill	uphill
Mass	0.51	0.54
Surface area	-0.17	-0.08
Mass-surface area	0.81	0.72

## DISCUSSION

### Comparisons Among Snowshoes

The small number of Marines makes any conclusions drawn from this study tentative. However, even with the small sample size, we found differences between the snowshoe models. The Montana had a significantly higher energy cost than the Pride or Standard snowshoes on the downhill portion of the course and this same trend was duplicated on the uphill portion of the course. The British snowshoe tended to have a higher energy cost than the Prides or Standards, but this was not statistically significant.

Because of the small number of subjects, we performed a statistical power analysis to further examine differences between the British snowshoe verses the Pride and Standard. The techniques of Cohen (1977) were used. An  $\alpha$  of 0.05 and power of 0.80 were assumed and effect sizes were calculated as  $\text{Mean}_1 - \text{Mean}_2 / \sigma$  (in which  $\sigma$  is the average of the standard deviations of the two means). Results are shown in Table 10. These results suggest that with larger sample sizes the Pride and Standard snowshoes could demonstrate lower energy cost than the British snowshoe.




Figure 9. The relationship of oxygen uptake and snowshoe mass-to-surface-area ratio.

Table 10

Statistical Power Analysis of Snowshoe Types Based on Data from  
This Study (assumes  $\alpha=0.05$  and power=0.80)

Course	Comparison	Effect size	Approximate sample size needed
Downhill	Standard versus British	0.53	50
	Pride versus British	0.46	50
Uphill	Standard versus British	0.85	20
	Pride versus British	0.24	138

The Montana snowshoe made walking most difficult for the Marines. This model tended to be very flexible since it was composed of automotive tire rubber. It could deform easily and tended to fold under often, causing the Marines to change their gait and stumble forward at times (although no one actually fell). Also, the Montana was wider than the other snowshoes, causing somewhat more abduction of the legs at the hips and more of a waddling gait than the other snowshoes. Gait adjustments and stumbling could have been significant factors in the higher energy cost. The Montana was also the heaviest of all the snowshoes and it has been shown that greater mass on the foot has a large effect on energy cost (Jones, Knapik, Daniels, & Toner, 1986; Jones et al., 1984).

The energy cost of the Pride and Standard snowshoes was lower than that of the Montana. The Pride and Standard shoes share two common characteristics. First, they have a hinge and binding system that allows the snowshoe to be dragged in the snow. With more of the snowshoe mass supported on the snow, less total mass (leg plus snowshoe) may have been lifted, thus reducing energy cost. The British and Montana had to be raised almost vertically out of the snow to avoid tripping. This additional vertical distance (relative to the Pride and Standard) may have contributed to the higher energy cost. The second common characteristic shared by the Pride and Standard shoes is an upturned front (the curved portion). This allows the snow to be pushed to the front and side, permitting the shoe to be elevated out of the depression in a more horizontal direction. This may also assist in reducing the vertical component of the leg-plus-snowshoe lift.

The correlational analysis suggested that a low mass-to-surface-area ratio is associated with a lower energy cost. Such a ratio would be achieved with a light snowshoe covering a large area of snow. Thus, reducing mass with lightweight materials while increasing surface area may be desirable in snowshoe design.

These data suggest that favorable characteristics of snowshoes from an energy cost perspective may be 1) a hinge and binding system that allows the snowshoe to be dragged across the snow, 2) an upturned front that pushes snow and allows a more horizontal displacement of the snowshoe, and 3) lightweight snowshoe materials combined with greater surface area. Further research will be necessary to determine the relative importance of these design characteristics, given the small number of Marines in this study.

### Comparisons Among Studies

Table 11 shows a comparison of the results of the present study with others that have examined the energy cost of snowshoeing. The difficulty of making direct comparisons is immediately apparent. There are differences in walking speed, and most studies do not report grade, depth of depression, or mass carried, despite the importance of these variables to energy cost (Goldman & Iampietro, 1962; Heinonen et al., 1959; Pandolf et al., 1976; Ramaswamy et al., 1966). Further, Rodgers et al. (1965) noted that energy cost will vary with the skill of the user; they reported that one of their subjects actually used more energy with snowshoes than without. Our Marines trained a full day with each snowshoe and were very familiar with them by the time the energy cost studies were conducted. In addition to these considerations, the findings here suggest that certain characteristics of the snowshoe can influence energy cost and none of the studies report these characteristics.

We used the Pandolf equation (Pandolf et al., 1977) to estimate the energy cost of walking in the snow, assuming the conditions of our study. This could only be done for the uphill portion of the course since the equation does not accurately estimate the metabolic rate for downhill walking (Knapik, Harman, & Reynolds, 1996). For the uphill calculation, we used a grade of 2.4% and a walking speed of 1.12 m/sec. The subject's load mass was the weight of the uniform plus the weight of the Oxylog2®. Terrain factors were calculated from the overall depression for each snowshoe (Pandolf et al., 1976). Metabolic rates were converted to kilocalories (kcal), assuming that 1 watt = 0.01433 kcal. Kilocalories were converted to oxygen uptake values, assuming that 1 liter of oxygen is the metabolic equivalent of 5 kcal (on the Oxylog2®). It was assumed that energy cost would increase 10% for each kg of snowshoe

weight (Jones et al., 1986; Jones et al., 1984). Values based on these assumptions are given in Table 12 and compared to actual energy cost values. The Pandolf equation underestimated the oxygen consumption rate by 7%, 16%, 11%, and 3% for the Pride, Montana, British, and Standard snowshoes, respectively. Note that the Pandolf equation was developed for walking in boots and has not been validated for snowshoes.

Table 11

The Energy Cost of Walking in Snowshoes in Various Studies  
(NR=not reported; CBC=cannot be calculated)

Study	Depression (cm)	Subject body (kg)	Grade (percent)	Speed (km/hr)	VO <sub>2</sub> (l/min)	VO <sub>2</sub> (ml/kg*min)
Buskirk et al. (1956)	NR	75	NR	3.7	1.28	17.5
Rodgers et al. (1965)	9	70	Near zero (on frozen river)	3.7	2.45	35.0
Allen & O'Hara (1973)	NR	NR	NR	2.0-3.6	0.97	CBC
Worsley et al. (1974) <sup>a</sup>	<5	67	NR	3.6 4.8	~1.3 ~1.7	~19 ~25
Present study (downhill)	5	73	-.24	4.0	1.22-1.46	16.8-20.2
Present study (uphill)	5	73	+2.4	4.0	1.51-1.78	21.0-24.5

<sup>a</sup>Authors noted that subjects had a pack but provided no pack mass; energy cost values estimate from equation  $(VO_2(\text{ml/kg*min}) = -1.3 + 0.33 * \text{speed}(\text{m/min}))$  and Figure V.2 in Worsley et al. (1974)

### Snow Conditions

Snow conditions were such that walking was not difficult for Marines in this study. The 8 cm of new snow was very soft and powdery. The 5 cm of average depression indicated that the snowshoes elevated Marines about 3 cm above the snow base. It will be critical in future studies to provide better descriptions and quantification of snow conditions, as these may alter energy cost measures.

Table 12

Estimates of Metabolic Rates, Energy Expenditure Rates, and  $\text{VO}_2$  (from Pandolf Equation)  
 Compared to Actual  $\text{VO}_2$  During Uphill Walking at 2.4% Grade

Snowshoe	<u>Estimates based on Pandolf equation</u>			Actual $\text{VO}_2$ (l/min)
	Metabolic rate (watts)	Energy expenditure rate (kcal/min)	$\text{VO}_2$ (l/min)	
Pride	504	7.22	1.47	1.58
Montana	508	7.28	1.50	1.78
British	504	7.22	1.47	1.62
Standard	495	7.09	1.46	1.51

## REFERENCES

- Adolph, E.F., & Molnar, G.W. (1946). Exchanges of heat and tolerances to cold in men exposed to outdoor weather. American Journal of Physiology, 146, 507-537.
- Allen, C.L., & O'Hara, W.J. (1973). Energy expenditure of infantry patrols during an arctic winter exercise (DCIEM Report No. 73-R-985). Downsview, Ontario, Canada: Defense and Civil Institute of Environmental Medicine.
- Askew, E.W. (1989). Nutrition for a cold environment. Physician and Sportsmedicine, 17(12), 13-21.
- Bobbert, A.C. (1960). Energy expenditure in level and grade walking. Journal of Applied Physiology, 15, 1015-1021.
- Borghols, E.A.M. (1978). Influence of heavy weight carrying on the cardiorespiratory system during exercise. European Journal of Applied Physiology, 38, 161-169.
- Buskirk, E.R., Kreider, M., Brebbia, R., Morana, N., Daniels, F., Welch, B.E., Insull, W., & Freideman, T.E. (1956). Caloric intake and energy expenditure in a sub-arctic environment (Technical Report No. EP-33). Natick, MA: Quartermaster Research and Development Center, U.S. Army.
- Buskirk, E.R., & Mendez, J. (1967). Nutrition, environment and work performance with special reference to altitude. Federation Proceedings, 26, 1760-1767.
- Catlin, M.J., & Dressendorfer, R.H. (1979). Effect of shoe weight on the energy cost of running. Medicine and Science in Sports, 11, 80.
- Cohen, J. (1977). Statistical Power Analysis for the Behavioral Sciences. New York: Academic Press.
- Goldman, R.F., & Iampietro, P.F. (1962). Energy cost of load carriage. Journal of Applied Physiology, 17, 675-676.
- Gordon, C.C., Churchill, T., Clauser, C.E., Bradtmiller, B., McConville, J.T., Tebbetts, I., & Walker, R.A. (1989). 1988 anthropometric survey of U.S. Army personnel: methods and summary statistics (Technical Report No. TR-89/044). Natick MA: U.S. Army Natick Research Development and Engineering Center.
- Haisman, M.F., & Goldman, R.F. (1974). Effect of terrain on the energy cost of walking with back loads and handcart loads. Journal of Applied Physiology, 36, 545-548.
- Heinonen, A.O., Karvonen, M.J., & Ruosteenoja, R. (1959). The energy expenditure of walking on snow at various depths. Journal of Applied Physiology, 2, 389-393.



- Hickey, C., Knapik, J., Ortega, S., & Nagel, J. (1996). Mobility and human factors evaluation and a research investigation to measure the energy cost of USMC candidate assault snowshoes (Technical Report in press). Aberdeen Proving Ground, MD: U.S. Army Research Laboratory.
- Hickey, C.A., Hanlon, W.E., & Oblak, T.H. (1994). Mobility and human factors evaluation of three prototype assault snowshoes (Technical Report No. ARL-TR-383). Aberdeen Proving Ground, MD: U.S. Army Research Laboratory.
- Jones, B.H., Knapik, J.J., Daniels, W.L., & Toner, M.M. (1986). The energy cost of women walking and running in shoes and boots. Ergonomics, 29, 439-443.
- Jones, B.H., Toner, M.M., Daniels, W.L., & Knapik, J.J. (1984). The energy cost and heart-rate response of the trained and untrained subjects walking and running in shoes and boots. Ergonomics, 27, 895-902.
- Knapik, J.J., Harman, E., & Reynolds, K. (1996). Load carriage using packs: a review of physiological, biomechanical and medical aspects. Applied Ergonomics, 27, 207-216.
- Legg, S.J., & Mahanty, A. (1986). Energy cost of backpacking in heavy boots. Ergonomics, 29, 433-438.
- Lohman, T.G., Roche, A.F., & Martorell, R. (1988). Anthropometric Standardization Reference Manual. Champaign, IL: Human Kinetics Books.
- Pandolf, K.B., Givoni, B., & Goldman, R.F. (1977). Predicting energy expenditure with loads while standing or walking very slowly. Journal of Applied Physiology, 43, 577-581.
- Pandolf, K.B., Haisman, M.F., & Goldman, R.F. (1976). Metabolic energy expenditure and terrain coefficients for walking on snow. Ergonomics, 19, 683-690.
- Patton, J.F., & Vogel, J.A. (1984). Effects of acute cold exposure on submaximal endurance performance. Medicine and Science in Sports and Exercise, 16, 494-497.
- Ramaswamy, S.S., Dua, G.L., Viswanathan, V.K., Madhavia, J., & Srivastava, T.N. (1966). Effects of looseness of snow on energy expenditure in marching on snow-covered ground. Journal of Applied Physiology, 21, 1747-1749.
- Rodgers, T.A., Buck, A.C., & Klopping, J.C. (1965). Studies on the energy cost of level cross-country travel in the arctic (Technical Report No. AAL-TR-65-9). Ft Wainwright, AK: Arctic Aeromedical Research Laboratory.
- Soule, R.G., & Goldman, R.F. (1969). Energy cost of loads carried on the head, hands, or feet. Journal of Applied Physiology, 27, 687-690.

- Soule, R.G., & Goldman, R.F. (1972). Terrain coefficients for energy cost prediction. Journal of Applied Physiology, 32, 706-708.
- Soule, R.G., Pandolf, K.B., & Goldman, R.F. (1978). Energy expenditure of heavy load carriage. Ergonomics, 21, 373-381.
- Stromme, S., Andersen, K.L., & Elsner, R.W. (1963). Metabolic and thermal responses to muscular exertion in the cold. Journal of Applied Physiology, 18, 756-763.
- Thompson, J.D. (1995). Infantry company operations in an extreme cold environment. Infantry, September-October.
- Virokannas, H. (1996). Thermal responses to light, moderate and heavy daily outdoor work in cold weather. European Journal of Applied Physiology, 72, 483-489.
- Vogel, J.A., Kirkpatrick, J.W., Fitzgerald, P.I., Hodgdon, J.A., & Harman, E.A. (1984). Derivation of anthropometry based body fat equations for the Army's weight control program (Technical Report No. 17-88). U.S. Army Research Institute of Environmental Medicine.
- Worsley, D. (1974). Physiological trial of cold weather clothing and equipment. Exercise Honky Tonk I. Norway 1974 (Technical Report No. 16/74). Farnborough, Hant (UK): Army Personnel Research Establishment, Royal Aircraft Establishment.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	ADMINISTRATOR DEFENSE TECHNICAL INFO CENTER ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218	1	COMMANDANT ARMY MED DEPT CENTER & SCHOOL ATTN HSHA FR BLDG 2840 FORT SAM HOUSTON TX 78236
1	DIRECTOR US ARMY RESEARCH LABORATORY ATTN AMSRL OP SD TA/ RECORDS MANAGEMENT 2800 POWDER MILL RD ADELPHI MD 20783-1197	1	JCS MED PLANS AND OPERATIONS DIV DEPUTY DIR FOR MED READINESS ATTN RAD SMYTH THE PENTAGON WASHINGTON DC 20310
1	DIRECTOR US ARMY RESEARCH LABORATORY ATTN AMSRL OP SD TL/ TECHNICAL LIBRARY 2800 POWDER MILL RD ADELPHI MD 20783-1197	1	HQDA OFFICE OF THE SURGEON GENERAL PREVENTIVE MED CONSULTANT ATTN MRMCMC PSP 5109 LEESBURG PIKE FALLS CHURCH VA 22041-3258
1	DIRECTOR US ARMY RESEARCH LABORATORY ATTN AMSRL OP SD TP/ TECH PUBLISHING BRANCH 2800 POWDER MILL RD ADELPHI MD 20783-1197	1	HQDA ASSIST SECY OF THE ARMY FOR RD&A ATTN SARD TM THE PENTAGON WASHINGTON DC 20310
1	COMMANDANT US ARMY PHYS FITNESS SCHOOL FT BENNING GA 31905	1	HQDA OFC OF THE SURGEON GENERAL ATTN DASG ZA 5109 LEESBURG PIKE FALLS CHURCH VA 22041-3258
1	OFFICE OF THE ASSISTANT SECY OF DEFENSE (HEALTH AFFAIRS) ATTN MEDICAL READINESS WASHINGTON DC 20301-1200	1	HQDA OFC OF THE SURGEON GENERAL ASSISTANT SURGEON GENERAL ATTN DASG RDZ/EXEC ASSIST ROOM 3E368 THE PENTAGON WASHINGTON DC 20310-2300
1	COMMANDER US ARMY MED RSCH & MATERIEL CMD ATTN MRMCMC OP FORT DETRICK FREDERICK MD 21701-5012	1	HQDA OFFICE OF THE SURGEON GENERAL ATTN DASG MS 5109 LEESBURG PIKE FALLS CHURCH VA 22041-3258
1	COMMANDER US ARMY MED RSCH & MATERIEL CMD ATTN MRMCMC PLC FORT DETRICK FREDERICK MD 20701-5012	1	DEAN SCHOOL OF MEDICINE UNIFORMED SERVICES UNIV OF HEALTH SCIENCES 4301 JONES BRIDGE ROAD BETHESDA MD 20814-4799
1	COMMANDER US ARMY MED RSCH & MATERIEL CMD ATTN MRMCMC PLE FORT DETRICK FREDERICK MD 20701-5012	1	STIMSON LIBRARY ARMY MED DEPT CENTER & SCHOOL ATTN CHIEF LIBRARIAN BLDG 2840 ROOM 106 FORT SAM HOUSTON TX 78234-6100

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDANT ARMY MED DEPT CENTER & SCHOOL ATTN DIR OF COMBAT DEVELOPMENT FORT SAM HOUSTON TX 78234-6100	1	COMMANDING OFFICER US NAVY CLOTHING & TEXTILE RESEARCH FACILITY ATTN NCTRF 01 NATICK MA 01760-5000
1	COMMANDER US ARMY AEROMEDICAL RSCH LAB ATTN MRMCMC UAX SI FORT RUCKER AL 36362-5292	1	COMMANDING OFFICER NAVY ENVIRON HEALTH CENTER 2510 WALMER AVENUE NORFOLK VA 23513-2617
1	COMMANDER US ARMY MED MATERIAL DEV ACTY ATTN MRMCMC UMZ FORT DETRICK FREDERICK MD 21701-5009	1	COMMANDING OFFICER NAVAL AEROSPACE MEDICAL INST (CODE 32) NAVAL AIR STATION PENSACOLA FL 32508-5600
1	COMMANDER US ARMY MED RSCH INST OF INFECTIOUS DISEASE ATTN MRMCMC UIZ FORT DETRICK MD 21701-5011	1	COMMANDING OFFICER NAVAL MEDICAL RSCH INST BETHESDA MD 20889
1	DIRECTOR WALTER REED ARMY INST OF RSCH ATTN MRMCMC UWZ C (DIR FOR RSCH MGMT) WASHINGTON DC 20307-5100	1	COMMANDING OFFICER NAVAL HEALTH RESEARCH CENTER PO BOX 85122 SAN DIEGO CA 92138-9174
1	COMMANDER US ARMY NATICK RD&E CENTER NATICK MA 01760-5000	1	COMMANDER ARMSTRONG MEDICAL RSCH LAB WRIGHT-PATTERSON AFB OH 45433
1	COMMANDER US ARMY RSCH INST FOR THE SOCIAL AND BEHAVIORAL SCIENCES 5001 EISENHOWER AVENUE ALEXANDRIA VA 22333-5600	1	COMMANDER USAF ARMSTRONG MED RSCH LAB ATTN TECHNICAL LIBRARY BROOKS AFB TX 78235-5301
1	COMMANDER US ARMY TRAINING & DOCTRINE CMD OFFICE OF THE SURGEON ATTN ATMD FORT MONROE VA 23651-5000	1	COMMANDER US AIR FORCE SCHOOL OF AEROSPACE MEDICINE BROOKS AFB TX 78235-5000
1	DIRECTOR BIOLOGICAL SCIENCES DIV OFC OF NAVAL RSCH - CODE 141 800 N QUINCY STREET ARLINGTON VA 22217	1	PM SOLDIER 14050 DAWSON BEACH ROAD WOODBIDGE VA 22191-1419
1	COMMANDING OFFICER NAVAL MED RSCH & DEV CMD ATTN NNMC/BLDG 1 BETHESDA MD 20889-5044	1	COMMANDING GENERAL US ARMY SAFETY CENTER FT RUCKER AL 36362
		1	COMMANDER US ARMY INFANTRY SCHOOL FT BENNING GA 31905

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER JFK SPECIAL WARFARE CENTER AND SCHOOL ATTN AOJK SU FT BRAGG NC 28307	1	HEADQUARTERS USATRADO ATTN ATCD SP FORT MONROE VA 23651
1	DIRECTOR ARMY PHYS FITNESS RSCH INST ARMY WAR COLLEGE CARLISLE BARRACKS PA 17013	1	COMMANDER USATRADO COMMAND SAFETY OFFICE ATTN ATOS (MR PESSAGNO/MR LYNE) FORT MONROE VA 23651-5000
1	DIRECTOR SPECIAL FORCES COMBAT DEVELOPMENTS FT BRAGG NC 28307	1	COMMANDER US ARMY MATERIEL COMMAND ATTN AMCAM 5001 EISENHOWER AVENUE ALEXANDRIA VA 22333-0001
1	DIRECTORATE FOR MANPRINT ATTN DAPE MR DEPUTY CHIEF OF STAFF PERSONNEL 300 ARMY PENTAGON WASHINGTON DC 20310-0300	1	COMMANDER USA OPERATIONAL TEST & EVAL AGENCY ATTN CSTE TSM 4501 FORD AVE ALEXANDRIA VA 22302-1458
1	OUSDA/DDDR&E(R&A)/E&LS PENTAGON ROOM 3D129 WASHINGTON DC 20301-3080	1	USA BIOMEDICAL R&D LABORATORY ATTN LIBRARY FORT DETRICK BUILDING 568 FREDERICK MD 21702-5010
1	CODE 1142PS OFFICE OF NAVAL RESEARCH 800 N QUINCY STREET ARLINGTON VA 22217-5000	1	HQ USAMRDC ATTN SGRD PLC FORT DETRICK MD 21701
1	WALTER REED ARMY INST OF RSCH ATTN SGRD UWI C (COL REDMOND) WASHINGTON DC 20307-5100	1	COMMANDER USA AEROMEDICAL RESEARCH LAB ATTN LIBRARY FORT RUCKER AL 36362-5292
1	DR ARTHUR RUBIN NATL INST OF STANDARDS & TECH BUILDING 226 ROOM A313 GAITHERSBURG MD 20899	1	US ARMY SAFETY CENTER ATTN CSSC SE FORT RUCKER AL 36362
1	COMMANDER US ARMY RESEARCH INSTITUTE ATTN PERI ZT (DR E M JOHNSON) 5001 EISENHOWER AVENUE ALEXANDRIA VA 22333-5600	1	AAMRL/HE WRIGHT PATTERSON AFB OH 45433-6573
1	DEFENSE LOGISTICS STUDIES INFORMATION EXCHANGE US ARMY LOG MGMT COLLEGE FORT LEE VA 23801-6034	1	US ARMY NATICK RD&E CENTER ATTN STRNC YBA NATICK MA 01760-5020
1	DEPUTY COMMANDING GENERAL ATTN EXS (Q) MARINE CORPS RD&A COMMAND QUANTICO VA 22134	1	US ARMY TROOP SUPPORT CMD NATICK RD&E CENTER ATTN BEHAVIORAL SCI DIV SSD NATICK MA 01760-5020

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	US ARMY TROOP SUPPORT CMD NATICK RD&E CENTER ATTN TECH LIBRARY (STRNC MIL) NATICK MA 01760-5040	1	MR RICHARD SHANNON KETRON INC WARMINSTER ATRIUM SUITE 203 600 LOUIS DRIVE WARMINSTER PA 18974
1	HQ USA RESEARCH INST OF ENVIRONMENTAL MEDICINE ATTN MEDRI CL (DR J KOBRICK) NATICK MA 01760-5007	1	PURDUE UNIVERSITY SERIALS UNIT CDM KARDEX 1535 STEWART CENTER WEST LAFAYETTE IN 47907-1535
1	DR RICHARD JOHNSON HEALTH & PERFORMANCE DIVISION US ARIEM NATICK MA 01760-5007	1	GOVT PUBLICATIONS LIBRARY 409 WILSON M UNIVERSITY OF MINNESOTA MINNEAPOLIS MN 55455
1	DR JON FALLESEN ARI FIELD UNIT PO BOX 3407 FORT LEAVENWORTH KS 66027-0347	1	DR RICHARD PEW BBN SYSTEMS AND TECH CORP 10 MOULTON STREET CAMBRIDGE MA 02138
1	COMMANDER USAMC LOGISTICS SUPPORT ACTIVITY ATTN AMXLS AE REDSTONE ARSENAL AL 35898-7466	1	DR ROBERT C SUGARMAN 132 SEABROOK DRIVE BUFFALO NY 14221
1	ARI FIELD UNIT FORT KNOX BUILDING 2423 PERI IK FORT KNOX KY 40121-5620	1	DR ANTHONY DEBONS IDIS UNIVERSITY OF PITTSBURGH PITTSBURGH PA 15260
1	USA TRADOC ANALYSIS COMMAND ATTN ATRC WSR (D ANGUIANO) WHITE SANDS MISSILE RANGE NM 88002-5502	1	DR ROBERT KENNEDY ESSEX CORPORATION SUITE 227 1040 WOODCOCK ROAD ORLANDO FL 32803
1	STRICOM 12350 RESEARCH PARKWAY ORLANDO FL 32826-3276	1	DR NANCY ANDERSON DEPARTMENT OF PSYCHOLOGY UNIVERSITY OF MARYLAND COLLEGE PARK MD 20742
1	COMMANDER USA COLD REGIONS TEST CENTER ATTN STECR TS A APO AP 96508-7850	1	MR LARRY W AVERY BATTELLE PACIFIC NW LABS PO BOX 999 MAIL STOP K6-66 RICHLAND WA 99352
1	US ARMY RSCH DEV STDZN GP-UK ATTN DR MIKE STOUT PSC 802 BOX 15 FPO AE 09499-1500	1	LIBRARY ESSEX CORPORATION SUITE 510 1430 SPRING HILL ROAD MCLEAN VA 22102-3000
1	INSTITUTE FOR DEFENSE ANALYSES ATTN DR JESSE ORLANSKY 1801 N BEAUREGARD STREET ALEXANDRIA VA 22311		

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	DR BEN B MORGAN DEPARTMENT OF PSYCHOLOGY UNIVERSITY OF CENTRAL FLORIDA PO BOX 25000 ORLANDO FL 32816
1	LAWRENCE C PERLMUTER PHD UNIV OF HEALTH SCIENCES THE CHICAGO MEDICAL SCHOOL DEPT OF PSYCHOLOGY 3333 GREEN BAY ROAD NORTH CHICAGO IL 60064
1	GENERAL DYNAMICS LAND SYSTEMS DIV LIBRARY PO BOX 1901 WARREN MI 48090
1	DR LLOYD A AVANT DEPARTMENT OF PSYCHOLOGY IOWA STATE UNIVERSITY AMES IA 50010
1	DR PAUL R MCCRIGHT INDUSTRIAL ENGINEERING DEPT KANSAS STATE UNIVERSITY MANHATTA KS 66502
1	DR MM AYOUB DIRECTOR INST FOR ERGONOMICS RESEARCH TEXAS TECH UNIVERSITY LUBBOCK TX 79409
1	MR KENNETH C CROMBIE TECHNICAL LIBRARIAN E104 DELCO SYSTEMS OPERATIONS 6767 HOLLISTER AVENUE GOLETA CA 93117
1	MR WALT TRUSZKOWSKI CODE 522.3 NASA/GODDARD SPACE FLIGHT CENTER GREENBELT MD 20771
1	DR NORMAN BADLER DEPT OF COMPUTER & INFORMATION SCIENCE UNIVERSITY OF PENNSYLVANIA PHILADELPHIA PA 19104-6389
1	DR DANIEL J POND BATTELLE PNL/K6-66 PO BOX 999 RICHLAND WA 99350

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HQDA (DAPE ZXO) ATTN DR FISCHL WASHINGTON DC 20310-0300
1	HUMAN FACTORS ENG PROGRAM DEPT OF BIOMEDICAL ENGINEERING COLLEGE OF ENGINEERING & COMPUTER SCIENCE WRIGHT STATE UNIVERSITY DAYTON OH 45435
1	PEO STANDARD ARMY MGMT INFORMATION SYSTEM ATTN AS PES STOP C-3 FT BELVOIR VA 22060-5456
1	PEO MGMT INFORMATION SYSTEMS ATTN AS PEM STOP C-2 BLDG 1465 FT BELVOIR VA 22060-5456
1	PEO INTELLIGENCE & ELECTRONIC WARFARE ATTN AMCPEO IEW VINT HILL FARMS STATION BLDG 197 WARRENTON VA 22186-5115
1	PEO COMMUNICATIONS ATTN SFAE CM RE FT MONMOUTH NJ 07703-5000
1	PROGRAM MANAGER RAH-66 4300 GOODFELLOW BLVD ST LOUIS MO 63120-1798
1	JON TATRO HUMAN FACTORS SYSTEM DESIGN BELL HELICOPTER TEXTRON INC PO BOX 482 MAIL STOP 6 FT WORTH TX 76101
1	CHIEF CREW SYSTEMS INTEGRATION SIKORSKY AIRCRAFT M/S S3258 NORTH MAIN STREET STRATFORD CT 06602
1	GENERAL ELECTRIC COMPANY ARMAMENT SYSTEMS DEPT RM 1309 ATTN HF/MANPRINT R C MCLANE LAKESIDE AVENUE BURLINGTON VT 05401-4985
1	JOHN B SHAFER 250 MAIN STREET OWEGO NY 13827

NO. OF COPIES	ORGANIZATION
1	OASD (FM&P) WASHINGTON DC 20301-4000
1	COMMANDER US ARMY MATERIEL COMMAND ATTN AMCDE AQ 5001 EISENHOWER AVENUE ALEXANDRIA VA 22333
1	COMMANDANT US ARMY ARMOR SCHOOL ATTN ATSB CDS (MR LIPSCOMB) FT KNOX KY 40121-5215
1	COMMANDER US ARMY AVIATION CENTER ATTN ATZQ CDM S (MR MCCracken) FT RUCKER AL 36362-5163
1	COMMANDER US ARMY SIGNAL CTR & FT GORDON ATTN ATZH CDM FT GORDON GA 30905-5090
1	PROJECT MANAGER SIGNALS WARFARE ATTN SFAE IEW SG (ALAN LINDLEY) BLDG P-181 VINT HILL FARMS STATION WARRENTON VA 22186-5116
1	COMMANDER MARINE CORPS SYSTEMS COMMAND ATTN CBGT QUANTICO VA 22134-5080
1	DIRECTOR AMC-FIELD ASSIST IN SCIENCE & TECHNOLOGY ATTN AMC-FAST (RICHARD FRANSEEN) FT BELVOIR VA 22060-5606
1	COMMANDER US ARMY FORCES COMMAND ATTN FCDJ SA BLDG 600 AMC FAST SCIENCE ADVISER FT MCPHERSON GA 30330-6000
1	COMMANDER I CORPS AND FORT LEWIS AMC FAST SCIENCE ADVISER ATTN AFZH CSS FORT LEWIS WA 98433-5000

NO. OF COPIES	ORGANIZATION
1	HQ III CORPS & FORT HOOD OFFICE OF THE SCIENCE ADVISER ATTN AFZF CS SA FORT HOOD TX 76544-5056
1	COMMANDER U.S. ARMY NATL TRAINING CENTER AMC FAST SCIENCE ADVISER ATTN AMXLA SA FORT IRWIN CA 92310
1	COMMANDER HQ XVIII ABN CORPS & FORT BRAGG OFFICE OF THE SCI ADV BLDG 1-1621 ATTN AFZA GD FAST FORT BRAGG NC 28307-5000
1	SOUTHCOM WASHINGTON FIELD OFC 1919 SOUTH EADS ST SUITE L09 AMC FAST SCIENCE ADVISER ARLINGTON VA 22202
1	HQ US SPECIAL OPERATIONS CMD AMC FAST SCIENCE ADVISER ATTN SOSD MACDILL AIR FORCE BASE TAMPA FL 33608-0442
1	HQ US ARMY EUROPE AND 7TH ARMY ATTN AEAGX SA OFFICE OF THE SCIENCE ADVISER APO AE 09014
1	COMMANDER HQ 21ST THEATER ARMY AREA CMD AMC FAST SCIENCE ADVISER ATTN AERSA APO AE 09263
1	COMMANDER HEADQUARTERS USEUCOM AMC FAST SCIENCE ADVISER UNIT 30400 BOX 138 APO AE 09128
1	HQ 7TH ARMY TRAINING COMMAND UNIT #28130 AMC FAST SCIENCE ADVISER ATTN AETT SA APO AE 09114



NO. OF  
COPIES ORGANIZATION

1 COMMANDER  
HHC SOUTHERN EUROPEAN TASK FORCE  
ATTN AESE SA BUILDING 98  
AMC FAST SCIENCE ADVISER  
APO AE 09630

1 COMMANDER  
US ARMY JAPAN/IX CORPS  
UNIT 45005 ATTN APAJ SA  
AMC FAST SCIENCE ADVISERS  
APO AP 96343-0054

1 AMC FAST SCIENCE ADVISERS  
PCS #303 BOX 45 CS-SO  
APO AP 96204-0045

1 COMMANDER ALASKAN COMMAND  
ATTN SCIENCE ADVISOR (MR GRILLS)  
6-900 9TH ST STE 110  
ELMENDORF AFB ALASKA 99506

1 MR GARY PERLMAN  
COMPUTER & INFORMATION SCIENCE  
OHIO STATE UNIV RM 228 BOLZ HALL  
2036 NEIL AVENUE  
COLUMBUS OH 43210-1277

1 DR SEHCHANG HAH  
DEPT OF BEHAVIORAL SCIENCES &  
LEADERSHIP  
BUILDING 601 ROOM 281  
US MILITARY ACADEMY  
WEST POINT NEW YORK 10996-1784

1 US ARMY RESEARCH INSTITUTE  
ATTN PERI IK (DOROTHY L FINLEY)  
2423 MORANDE STREET  
FORT KNOX KY 40121-5620

1 ARL HRED ARDEC FIELD ELEMENT  
ATTN AMSRL HR MG (R SPINE)  
BUILDING 333  
PICATINNY ARSENAL NJ 07806-5000

1 ARL HRED ATCOM FIELD ELEMENT  
ATTN AMSRL HR MI (A MANCE)  
4300 GOODFELLOW BLVD  
BLDG 105 1ST FLOOR POST A-7  
ST LOUIS MO 63120-1798

1 ARL HRED CECOM FIELD ELEMENT  
ATTN AMSRL HR ML (J MARTIN)  
MYERS CENTER ROOM 3C214  
FT MONMOUTH NJ 07703-5630

NO. OF  
COPIES ORGANIZATION

1 ARL HRED MICOM FIELD ELEMENT  
ATTN AMSRL HR MO (T COOK)  
BUILDING 5400 ROOM C242  
REDSTONE ARSENAL AL 35898-7290

1 ARL HRED AVNC FIELD ELEMENT  
ATTN AMSRL HR MJ (R ARMSTRONG)  
PO BOX 620716 BUILDING 514  
FT RUCKER AL 36362-0716

1 ARL HRED FT HOOD FIELD ELEMENT  
ATTN AMSRL HR MA (E SMOOTZ)  
HQ TEXCOM BLDG 91012 RM 134  
FT HOOD TX 76544-5065

1 USARL HRED FIELD ELEMENT  
USAADASCH  
ATTN ATSA CD  
ATTN AMSRL HR ME (K REYNOLDS)  
5800 CARTER ROAD  
FORT BLISS TX 79916-3802

1 ARL HRED ARMC FIELD ELEMENT  
ATTN AMSRL HR MH (M BENEDICT)  
BUILDING 1109D (BASEMENT)  
FT KNOX KY 40121-5215

1 ARL HRED USAFAS FIELD ELEMENT  
ATTN AMSRL HR MF (L PIERCE)  
BLDG 3040 ROOM 220  
FORT SILL OK 73503-5600

1 ARL HRED USAIC FIELD ELEMENT  
ATTN AMSRL HR MW (E REDDEN)  
BUILDING 4 ROOM 349  
FT BENNING GA 31905-5400

1 ARL HRED USASOC FIELD ELEMENT  
ATTN AMSRL HR MN (F MALKIN)  
BUILDING D3206 ROOM 503  
FORT BRAGG NC 28307-5000

1 ARL HRED SC&FG FIELD ELEMENT  
ATTN AMSRL HR MS (L BUCKALEW)  
SIGNAL TOWERS ROOM 207  
FORT GORDON GA 30905-5233

1 ARL HRED FT HUACHUCA FIELD  
ELEMENT  
ATTN AMSRL HR MY  
BUILDING 84017  
FORT HUACHUCA AZ 85613-7000

NO. OF  
COPIES    ORGANIZATION

- 1     ARL HRED FIELD ELEMENT AT  
      FORT BELVOIR  
      STOP 5850 ATTN AMSRL HR MK  
      (P SCHOOL)  
      10109 GRIDLEY ROAD SUITE A102  
      FORT BELVOIR VA 22060-5850
  
- 1     ARL HRED TACOM FIELD ELEMENT  
      ATTN AMSRL HR MU (M SINGAPORE)  
      BUILDING 200A 2ND FLOOR  
      WARREN MI 48397-5000
  
- 1     ARL HRED STRICOM FIELD ELEMENT  
      ATTN AMSRL HR MT (A GALBAY)  
      12350 RESEARCH PARKWAY  
      ORLANDO FL 32826-3276
  
- 1     ARL HRED OPTEC FIELD ELEMENT  
      ATTN AMSRL HR MR  
      PARK CENTER IV RM 1450  
      4501 FORD AVENUE  
      ALEXANDRIA VA 22302-1458
  
- ABERDEEN PROVING GROUND
  
- 2     DIRECTOR  
      US ARMY RESEARCH LABORATORY  
      ATTN AMSRL OP AP L (TECH LIB)  
      BLDG 305 APG AA
  
- 1     LIBRARY  
      ARL BUILDING 459  
      APG-AA
  
- 1     ARL SLAD  
      ATTN AMSRL BS (DR JT KLOPCIC)  
      BLDG 328 APG-AA
  
- 1     CHIEF ARL HRED ERDEC FIELD  
      ELEMENT  
      ATTN AMSRL HR MM (D HARRAH)  
      BLDG 459  
      APG-AA
  
- 1     USMC LIAISON OFFICE  
      ATTN AMST ML  
      RYAN BUILDING APG-AA

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE October 1996		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE  Energy Cost of Walking in Four Types of Snowshoes				5. FUNDING NUMBERS  AMS Code 622716.H700011 PR: 1L162716AH70 PE: 6.27.16	
6. AUTHOR(S)  Knapik, J.J.; Hickey, C. A. Jr.; Ortega, S.V. Jr.; Nagel, J.R.; de Pontbriand, R.					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army Research Laboratory Human Research & Engineering Directorate Aberdeen Proving Ground, MD 21005-5425				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army Research Laboratory Human Research & Engineering Directorate Aberdeen Proving Ground, MD 21005-5425				10. SPONSORING/MONITORING AGENCY REPORT NUMBER  ARL-TR-1175	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution is unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Energy cost was examined while four Marines walked at 4 km/hr on an open field with each of four snowshoes. Snowshoes were the Pride Assault, Montana, British Assault, and the U.S. Army Standard. The grade of the field was about 2.4% and the Marine walked once downhill and once uphill with each snowshoe. Expired respiratory gases were collected continuously during each walk. On the downhill portion of the course, average $\pm$ standard deviation (SD) $\text{VO}_2$ values were $1.25 \pm 0.13$ , $1.46 \pm 0.11$ , $1.31 \pm 0.13$ , and $1.22 \pm 0.20$ l/min for the Pride, Montana, British, and Standard snowshoes, respectively ( $p=0.01$ ); the Pride and Standard snowshoes had significantly lower energy cost than the Montana ( $p=0.05$ ). On the uphill portion of the course, average $\pm$ SD $\text{VO}_2$ values were $1.58 \pm 0.12$ , $1.7 \pm 0.14$ , $1.62 \pm 0.21$ , and $1.5 \pm 10.06$ l/min for Pride, Montana, British, and Standard snowshoes, respectively ( $p=0.06$ ). Data suggested that several characteristics may be favorable from an energy cost perspective: 1) a foot hinge and binding system that allows the snowshoe to be dragged across the snow, 2) an upturned front that pushes snow away and allows a more horizontal displacement of the snowshoe during locomotion, and 3) a lower mass-to-surface-area ratio. Further research will be necessary to determine the relative importance of these design characteristics, given the small number of subjects.					
14. SUBJECT TERMS  heart rate                      ventilation military personnel				15. NUMBER OF PAGES 50	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT  Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE  Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT  Unclassified	20. LIMITATION OF ABSTRACT		